

TF3 HD – Random Access

Easily integrates with your machine to add tray automation.
Handles large format trays, custom trays, and Thermoform trays.

- ✓ International Design DM/239750 Wipo
- ✓ EMC/EMV TuV Rheinland

LARGE FORMAT TRAY FEEDER

The **TF3-HD** is our largest tray feeder. It is designed to automatically feed custom-sized trays, thermoform trays, and multiple tray types in a single production run. Trays are loaded onto carrier plates into a cassette. This keeps the trays flat and supported during production. It loads and unloads tray sizes that fit on the 400 × 300 mm sheet to and from your machine. Multiple smaller trays can fit on one sheet, which increases production between tray exchanges and operator reloading time. Reloading can be done while your machine is running, so production is not interrupted.

- ✦ Random Access Cassette load tray feeder
- ✦ Handles thermoform trays in steel sheets
- ✦ Handles numerous ≤ 400×300 mm trays
- ✦ Very compact form factor
- ✦ Pay load 45 kg for increase autonomy
- ✦ Operator friendly loading/unloading
- ✦ Easy to integrate, standalone device
- ✦ Loads two JEDEC trays at a time with a 40-tray capacity



CONFIGURATION (HW/SW)

- ✦ **Conveyor Standard Length** 550mm, 700 mm
- ✦ **Custom Conveyor** available
- ✦ **“Open End” Conveyor** available
- ✦ **Door** swing left or right (standard swing left)
- ✦ **Communication Signals** serial UDP/IP, TCP/IP, RS232, RS485, SMEMA and DIO (limited)
- ✦ **Protocol** Basic or Extended
- ✦ **Swiss Made**

Easily Integrates With:

SMT Assembly Equipment
Singulation Equipment
Device Programmers
Test Handlers
Die Bonders
Inspection Equipment

JTF3 PLUS

JEDEC Tray Feeder

- ✓ International Design DM/239750 Wipo
- ✓ EMC/EMV TuV Rheinland

TECHNICAL SPECIFICATION

Magazine Capacity

20 Tray Slots, Pitch=22.5 mm
10 Tray Slots, Pitch=45 mm
Custom cassettes available

Load

Max stack weight of 90kg (198lbs)
Max tray/carrier weight of 4kg (8.8lbs)

Allowable Loading Height

450mm (17.7")

Tray Cycle Time

Ca. 7–12 seconds typical, application dependent

Position Accuracy

± 50 µm (carrier plate)

Flexibility

Microprocessor controlled, adjustable conveyor speed, tray changeover

Electrical

24 VDC ± 10 %, ~7A

Compressed Air

6 Bar (87 psi)

Feeder Weight


95 kg (210 lbs.)

Environment

10–35°C / 10–90 % R.H.

Standards Compliance

SEMI S2 & S8, NFPA 70 & 79, CE



SCOPE OF DELIVERY

- ✦ 1x TF3 Feeder
- ✦ 1x Cassette 20 Slots
- ✦ 20x carrier plate optional

FUTURE OPTION

- ✦ Cassette loading using slides
- ✦ Feeder accepts a Cassette from an AGV

QUASYS AG

Rothusstrasse 5a
CH-6331 Hünenberg
Switzerland
sales@quasys.ch

North & South America

Powatec USA, Inc.
Erik Mori
e.mori@powatec.com
trayfeeders.com